

**Telescopic
Novy Fusion Pro 90 cm
Anthracite**



EAN 5414425203451

Energy label

▪ Energy Efficiency class (EEIhood)	A
▪ Annual Energy Consumption (kWh/year) (AEChood)	39
▪ Fluid Dynamic Efficiency class (FDEhood)	A
▪ Lighting Efficiency class (LEhood)	A
▪ Grease Filtering Efficiency class (GFEhood)	C

Functions & features

▪ Motor	Integrated
▪ Sound absorber	Integrated
▪ Recirculation	Optional
▪ InTouch function	Standard
▪ Auto stop	▪
▪ Delayed switch off (minutes)	10
▪ Grease filter	8740050
▪ Number of grease filters	3
▪ Grease filter cleaning indication	▪
▪ Recirculation filter cleaning indication	▪
▪ Control method	Touch control
▪ Number of speeds	3 + power
▪ Automatic Power revert (minutes)	6

Dimensions

▪ Product dimensions (WxDxH) (mm)	900 x 310 x 340
▪ Dimensions cut-out opening (WxD) (mm)	x
▪ Min dimensions cabinet (WxDxH) (mm)	900 x 310 x 340
▪ Suitable for installation in a bottomless cabinet	▪
▪ Advised mounting height induction hobs (Hmin-Hmax) (mm)	500 - 750
▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 750
▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)	500 - 750
▪ Diameter outlet (mm)	150
▪ Position exhaust	Top

Lighting

▪ Functional lighting type	Led strip
▪ Functional light dimmable	▪
▪ Number of functional lights	2
▪ Total energy consumption functional light (W)	18
▪ Color functional light (K)	3000

Airflow and noise level





▪ Free airflow (m ³ /h)	815
▪ Airflow (m ³ /h) measured according to EN 61591	

Airflow and noise level

- Sound regulation according to EN 60704-2-13
- Airflow duct out speed 1 (m³/h) / Max pressure duct out speed 1 (Pa) 391 / 178
- Airflow duct out speed 2 (m³/h) / Max pressure duct out speed 2 (Pa) 535 / 356
- Airflow duct out speed 3 (m³/h) / Max pressure duct out speed 3 (Pa) 606 / 383
- Airflow duct out max powerspeed (m³/h) (Qboost) / Max pressure duct out674 / 383
max powerspeed (Pa)
- Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 36 / 48
1 (dB(A))
- Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 44 / 56
2 (dB(A))
- Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 47 / 59
3 (dB(A))
- Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct 50 / 62
out at max powerspeed (dB(A)) (LWAbost)

Technical specifications

- | | |
|---|------|
| ▪ Maximum power (W) | 124 |
| ▪ Voltage appliance (V) | 230 |
| ▪ Frequency (Hz) | 50 |
| ▪ Power consumption in stand-by-mode (Ps) (W) | 0,25 |
| ▪ Net weight (kg) | 14,5 |
| ▪ Length power supply cable (m) | 1,1 |



Installation accessories

Back panel & chimney extensions

- 88408160 Chimney extension Novy Fusion Pro

Additional accessories

- 840029 Remote control (optional)

Accessories

Recirculation kit



8740400

Monoblock recirculation set Novy Fusion Pro



906450

Exhaust grill for upper cabinet black

